LIST B

11.1.6	LIST B			
List of anticipated requirements of GENERAL/COMMON STOCK/CODED				
	ITEMS for 3 YEARS (EAST YARD)			
Sr.No.	Brief Discription of Material/Services	EstimatedQty.Reqd.		
1	LAMP, GAS FILLED B.C.CLEAR ELMI	60000 EA 1800 EA		
	RING 110 V /60 W, AS PER IS-418.			
2	LAMP, GAS FILLED B.C.CLEAR.ELMI RING, 230V/60W			
	SWITCHES FLUSH PIANO TYPE NON	4500 EA		
3	WATERTIGHT 5 AMPS/250V. IS			
	CERTIFIED.			
4	HAND LAMP, WOODEN COMPLETE WITH B.C.HOLDERS,IRON GUARDS AND	1800 EA		
4	HOOKS.	1800 LA		
	COPPER CONDUCTOR PVC/PVC SHEATHS			
5	660V GR 4 CORE X 4 SQMM (56/0.300MM)	6000 M		
	IS694/77, SUPPLIER TO PROVIDE IS	OUUU MI		
	CERTIFICATE.			
	1.5 SQ.MM (30/0.250 MM) PVC INSULATED			
	4 CORE COPPER CONDUCTOR			
6	FLEXIBLEWIRE IN 660 V/1100 V GRADE	3000 M		
	AS PER IS:694/1977 AND 1990 SUPPLIER			
	TOPROVIDE IS CERTIFICATE			
	TELEPHONE CABLE,(COLOUR CODE) PVC			
	INSULATED & PVC SHEATHED			
7	ATCCONDUCTORCONFORM TO ITD	1500 M		
	SPEC.S/WS-113B, 20 PAIR (.51MM),(ENDS			
	TO BE SUITABLYSEALED)			
8	WIRE, PVC INSULATED 2 CORE, FLEXIBLE COPPER CONDUCTOR WIRE	6000 M		
	24/0.2 MM(0.75 MM)660 /1100 V			
	CONFORMING TO IS 694/1977 & 1990			
	PVC INSULATED, 3 CORE FLEXIBLE			
9	COPPER CONDUCTOR WIRE,24/0.2 MM	6000 3.6		
	(0.75 MM), 660 /1100 V, CONFIRMING TO IS	6000 M		
	694/1977&1990.			
10	WIRE, SINGLE PVC, 3/22 OR 3/0.029, 660V,	6000 M		
	SUPPLIER TO PROVIDE ISCERTIFICATE	OUUU IVI		
11	WIRE, SINGLE PVC, 7/0.029, 660V.	1500 M		
12	WIRE, PVC/PVC, 7/0.029, 660V	1500 M		
	WIRE, PVC INSULATED COPPER			
	CONDUCTOR WIRE SINGLE CORE,			
13	7/0.036/660VCONFIRMING TO BS 2004/IS	3000 M		
	694/1977 & 1990,IN FOUR			
	COLOURS(RED, YELLOW, BLUE & BLACK)			
	SUPPLY SHOULD BE IN EQUAL			
	OUANITTY OFALLCOLOURS.			

	WIRE, PVC INSULATED COPPER	
14	CONDUCTOR, SINGLE	
	CORE,7/0.064/660VCONFIRMING TO BS-	
	2004/IS 694/1977 & 1990. IN FOUR	1500 M
	COLOURS(RED,YELLOW,BLUE & BLACK)	
	SUPPLY SHOULD BE IN EQUAL	
15	OUANTITY OFALLCOLOURS.	
	WIRE, PVC, 2 CORE, FLEXIBLE 50/0.25MM	
	COPPER CONDUCTOR, 1100 VOLT	1500 M
	GRADE,IN COILS OF 100 MTRS, AS PER IS	
	694 / 1990.	
	WIRE, 2.5 SQ MM (50/0.25 MM) PVC	
	INSULATED 3 CORE COPPER	
16	CONDUCTORFLEXIBLE WIRE IN 660	3000 M
10	V/1100 V GRADE . AS PER IS 694/1977 AND	
	1990,SUPPLIER TO PROVIDE IS	
	CERTIFICATE.	
	WIRE, PVC, 24/0.2 MM,INSULATED TWIN	
	TWISTED COPPER CONDUCTOR	
17	FLEXIBLEWIRE IN 1100 V, GRADE (RED	2000 M
17	AND BLACK) CONFIRM TO IS 694/1977	3000 M
	&1990 &ISI MARKED SUPPLIER TO	
	PROVIDE IS CERTIFICATE.	
	PVC INSULATION ADHESIVE TAPE AS	
18	PER IS 7809 PART III, SECTION-I OF	1000 ROL
	1986,2.5 CM*25 MTRS, RED.	
	TAPE, PVC INSULATION ADHESIVE TAPE	
19	AS PER IS 7809 PART III,SECTION I	1000 ROL
	OF1986. 2.5 CMS X 25 MTRS, YELLOW.	
	TAPE, PVC INSULATION ADHESIVE TAPE	
20	AS PER IS 7809 PART III, SECTION I	1000 ROL
	OF1986 2.5 CMS X 25 MTRS, BLUE.	
	TAPE, PVC INSULATION ADHESIVE TAPE	
21	AS PER IS 7809 PART III,SECTION I OF1986	1000 ROL
	2.5 CMS X 25 MTRS. BLACK	
	FILTERS FOR RESPIRATORS,(400 NOS IN	
	A BUNDAL) OVER ALL SIZE 5 1/2 INCH X3	
	1/2 INCH,WEIGHT OF SURGICAL COTTON	
22	UNIFORELY SPREAD 1.8MM	1500 EA
22	GRAMS,(MIN)FREE FROM FOREIGN	1300 L/1
	PARTICLES, DUST ETC OUTSIDE CLOTH	
	WHTE BLEACHED GOUGEDCLOTH WITH	
	UNIFORM PERFORATION.	
	COTTON FACE COVER FOR	
	FILTER,OVERALL SIZE 6INCH X 4 INCH	
	(155MM X108MM) WITH UNBLE ACHED	
23	COTTON TAPE, WIDTH OF TAPE 8 TO 13	3000 EA
	MM,AND MINIMUM11 INCH LONG	
	PROTRUDED PORTION (IN A BUNDLE OF	
	100 NOS)	
24	PARTICULATE RESPIRATOR WITH	
	ELECTROSTATIC FILTER FOR	3000 EA
	FILTERINGEFFICIENCY OF 0.3 MICRONS	
25	CONFIRMING BIS 9473-1980.	0400 1
25	BRILLENT GREEN	8400 L

26	GOLDEN YELLOW	2400 L
27	POST OFF RED	1200 L
28	AZURE BLUE	2100 L
29	WHITE ENAMEL	3000 L
30	WHITE FLAT	1500 L
31	WHITE DISTEMPER	1500 KG
32	ROLLER BRUSH 6"	1800 N
33	ROLLER BRUSH 4"	1800 N